

BEST AVAILABLE COPY

707/G62004/003061



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport

South Wales
NP10 80Q

REC'D 07 SEP 2004

WIPO


PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Stephen Hendley

Dated 31 August 2004

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Patents Form 1/77

Patents Act 1977
(Rule 16)



15JUL03 E822751-1 002813
P01/7700 0.00-0316523.0

1/77

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

THE PATENT OFFICE
WM
15 JUL 2003
RECEIVED BY FAX

The Patent Office
Cardiff Road
Newport
South Wales
NP10 8QQ

1.	Your Reference	P58931F-GB		
2.	Patent Application number (The Patent Office will fill in this part)	15 JUL 2003	0316523.0	
3.	Full name, address and postcode of the or each applicant (underline all surnames)	see attached sheet for details of three applicants		
	Patents ADP Number (if you know it)	08673519001		
	If the applicant is a corporate body, give the country/state of its incorporation	08673525001		
		08673550001		
4.	Title of the invention	SPRAY APPARATUS		
5.	Name of your agent (if you have one)	FRY HEATH & SPENCE LLP		
	"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	The Gables Massetts Road Horley Surrey RH6 7DQ United Kingdom		
	Patents ADP Number (if you know it)	05880273001	08459554001	
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (if you know it) the or each application number.	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application.	Number of earlier application	Date of filing (day / month / year)	
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:	No		
	a) any applicant named in part 5 is not an inventor; or			
	b) there is an inventor who is not named as an			
	c) applicant, or			
	d) any named applicant is a corporate body			
	(See note (d))			

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document.

Continuation sheets of this form 0

Description 5

Claim(s) 0

Abstract 0

Drawing(s) 1

10. If you are also filing any of the following, state how many against each item.

Priority documents 0

Translations of priority documents 0

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 0

Request for preliminary examination and search (Patents form 9/77) 0

Request for substantive examination (Patents form 10/77) 0

Any other documents (please specify) 0

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

Fry Heath & Spence LLP 15 July 2003

12. Name and daytime telephone number of person to contact in the United Kingdom A.V. Fry - 01293 776880

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you filing or applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
 - Write your answers in capital letters using black ink or you may type them.
 - If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
 - If you have answered 'Yes' Patents Form 7/77 will need to be filed.
 - Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Full name, address and postcode of the or each applicant:

1 DALY, David
54 Sunnydale
London
SE12 8JN 0867351 9001

2 ABEL, Christina
54 Sunnydale
London
SE12 8JN 08673535001

3 ENNIS, Alan
1 Fayreholme Cottages
Godstone
Surrey
RH9 8LN 0867355 0001

SPRAY APPARATUS

This invention relates to spray apparatus for cleaning *inter alla* toilet bowls, urinals and bidets where hygiene is paramount. For ease of reference these items will be referred to below as toilet bowls.

Conventionally brushes are used in houses, hotels and elsewhere to clean the surfaces of toilet bowls. Whereas these brushes may well adequately clean a toilet bowl, they in themselves harbour germs and other debris to the potential harm of people or children who come into contact with them.

The present invention set outs to provide an alternative non contact cleaner for toilet bowls which overcomes, or at least alleviates, many of the disadvantages present in existing toilet bowl cleaners.

In one aspect, the invention provides spray apparatus for cleaning *inter alla* toilet bowls, the apparatus comprising a spray head connected through a water hose to a pressurised source of water, the spray head including a casing formed with an opening to receive one end of the water hose and an outlet nozzle from which water under pressure can leave the housing, and a hand operated valve for selectively enabling or preventing the flow of water through the outlet nozzle.

The cross-sectional area of the outlet nozzle is preferably substantially less than that of the hose and/or the opening in communication with the hose. Typically, the cross-sectional area of the outlet nozzle is less than one half that of the hose.

The outlet nozzle may comprise a single orifice or a plurality of such orifices typically in the form of a compact pattern. In a preferred arrangement, four orifices are provided.

A chamber may be housed within the casing to receive and retain cleansing medium. The cleansing medium may comprise a cleansing tablet, e.g. an anti-microbial tablet.

The valve may be operated manually by a trigger mounted externally on the spray head casing. The valve may be resiliently biased to its closed position. That is to say, the outlet nozzle of the spray head is only placed in communication with the pressurised source of water through operation of the trigger by, for example, finger pressure. The biasing of the valve may be effected by a coil spring.

The water hose is preferably flexible and may be produced from plastics, rubber or rubber-like material. The hose wall may be reinforced with metallic wire or filaments.

The spray head is preferably produced from plastics and may include a removable cover to provide access to the chamber. Materials other than plastics may however be employed.

The hose is preferably connected to the head through a friction fit over a collar protruding from one side of the casing. The external surface of the hose may be corrugated.

The source of pressurised water may comprise a pipe connected to a mains supply to a building. Alternatively, the pipe may receive water from an elevated holding tank positioned within a building. Alternatively, the pipe may receive water from a pipe connected to receive water under pressure from, for example, an electrically or mechanically driven pump. In one arrangement, the pipe comprises a water feed pipe for conveying

water under pressure to a cistern of a toilet. The connection between the hose and the water pipe may comprise a conventional bifurcated or similar connector.

The invention will now be described by way of example only, with reference to the accompany diagrammatic drawing of spray apparatus in accordance with the invention, in which Figure 1 is a perspective view of spray apparatus in accordance with the invention.

The illustrated apparatus comprises a spray head 1 connected to a water hose 2. The spray head has a casing 3 and the hose 2 includes a corrugated end piece 4 which projects into an inlet orifice of the casing 3. The hose defines a friction fit within the inlet orifice of the casing. The casing 3 houses a chamber including a compartment in which is positioned a cleansing tablet. This tablet may comprise an anti-microbial tablet.

The casing has a removable lid 8 to provide access to the chamber.

In use, the chamber is flooded with water entering the casing through the inlet orifice, the water leaving the casing through an outlet nozzle 9 positioned in the side of the casing 3 remote from the inlet orifice. The outlet nozzle carries a series of orifices 10. The sum of the cross-sectional areas of the orifices 10 is substantially less than that of the hose and/or the inlet orifice, typically the total area of the outlet nozzle is less than half that of the hose and/or the inlet orifice.

The flow of water through the casing is controlled by a valve operable by a trigger 11 positioned on the external surface of the spray head. The trigger 11 is typically operated by finger pressure. The valve is biased to a position in which it prevents the flow of water to the outlet nozzle. Thus, operation of the trigger enables water to pass from the hose, through the casing and then to the outlet nozzle.

A rod-shaped extension piece may be connected to the spray head to enable the jets of water leaving the nozzle orifices 10 to be directed at locations within a toilet bowl and even below the surface of water retained in the bowl. The extension piece preferably includes a plurality of generally parallel bores, each receiving water from one of the outlet orifices of the spray head. One end of the extension piece may be formed with a screw thread which cooperates with a complementary thread of the spray head. Other ways of removably mounting the extension piece onto the spray head may be used.


The end of the hose 2 remote from the spray head is connected via a conventional bifurcated coupling to a pipe connected to receive water from a pressurised source. Typically this source comprises a mains supply or a header tank of a building. It may alternatively comprise a supply of water pumped to the pipe by an external electronically or mechanically operated pump.

The respective dimensions of the hose, the inlet orifice and the outlet nozzle are selected to ensure that water leaving the spray head does so at a pressure sufficient to effect satisfactory cleaning of the toilet bowl.

When not in use, the spray head is simply mounted close to the respective toilet bowl. For use, it is simply lifted and the nozzle directed towards the bowl interior and the trigger operated to provide effective cleansing thereof. After use, the spray head is simply returned to its inoperative position. Because there is no contact between the spray head and the bowl interior, problems normally associated with toilet bowl brushes are avoided.

It will be appreciated that the foregoing is merely exemplary of spray apparatus in accordance with the invention and that various

modifications can readily be made thereto without departing from the true scope of the invention described.



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.